

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION****Craig's Custom Motorcycles Inc.**3300 E. Harrisburg Pike
Middletown, Pa. 17057

Phone:717-944-9141

Fax:717-944-9452

Emergency Telephone: 1-800-424-9300 (24 hours, CHEMTREC)

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS Number	%	OSHA		TWA		STEL		Ceiling	
			ACGIH	ppm	mg/m3	ppm	mg/m3	ppm	mg/m3	
Bisphenol A/Epichlorohydrin Based Epoxy Resin	025068-38-6	90 - 100								

3. HAZARDS IDENTIFICATION

Effects of Overexposure Repeated contact or breathing of vapors may cause irritation; material is also a strong sensitizer. Eye and skin contact may cause transient irritation.

4. FIRST AID MEASURES

Eyes	Flush with water, get medical attention.
Skin	Wash with soap and water; remove contaminated clothing.
Inhalation	Remove to fresh air.
Ingestion	No known antidote but give milk or water; induce vomiting if large amount swallowed.

5. FIREFIGHTING MEASURES

Flashpoint	> 480°F
Flashpoint Method	PMCC
Extinguishing Media	Dry chemicals, chemical foam, carbon dioxide, water.
Special Firefighting Measures	Avoid breathing smoke. Addition of water may reduce flame intensity.
Fire and Explosion Hazards	Toxic gases may be liberated; handle as combustible; store in a cool place.
Flammable Limits	N/A
LEL	N/A
UEL	N/A

6. ACCIDENTAL RELEASE MEASURES

Spill and Leak Procedures	Prevent skin and eye contact. Soak up in absorbent material or scrape up and transfer to disposal container. Wipe up remaining residue with solvents observing solvent flammability cautions, or use detergents.
---------------------------	--

7. HANDLING AND STORAGE

Handling and Storage	For industrial use only. WARNING: May cause sensitization, irritation or other allergic responses. Avoid eye and/or skin contact and prolonged inhalation of vapors.
Special Sensitivity	Store in a cool place in closed containers. Handle per Hazard Potential of hardener.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION